
REVISIONS							
	REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	
	1		RELEASED FOR PRODUCTION.	6/17/2016	DPD	JAG	
	2	16-0180	-13, -15 CH'D MAT'L WAS 1018/1020 CR IS A36/1018/1020 HR27, -29 CH'D MAT'L WAS Y-20, BLACK IS ETHAFOAM 220, BLACK, CH'D VENDOR WAS (I.R. SPECIALTY) IS (CASE SOLUTIONS)27 DELETED DIM 4X R.72, ADDED DIMS 4X 1.00, 4X 45°, -29 DELETED DIM 4X R.45, ADDED DIMS 4X .63, 4X 45°,	10/20/2016	DPD	JAG	



ASSY QTY	ASSY QTY	ASSY QTY	B/O	Part #	UNIT QTY	Description	Material	B/O INFORMATION OR SPECIFICATIONS	PG.
		Χ		-1	1	LATERAL ELASTOMERIC BEARING BOLT EXCHANGE			2
		- 1		-3		LATERAL BASE	1018/1020 CR		3
		1		-5		LATERAL PAD	WHITE DELRIN/ACETAL		4
		1		-7		LATERAL CLAMP PLATE	6061		5
	Χ			-9	1	LONGITUDINAL ELASTOMERIC BEARING BOLT EXCHANGE			6
	1			-11		LONGITUDINAL BACK PLATE	1018/1020 CR		7
	1			-13		LONGITUDINAL BASE PLATE	A36/1018/1020 HR		8
	1			-15		LONGITUDINAL BOLT PLATE	A36/1018/1020 HR		9
	1			-17		LONGITUDINAL PAD	WHITE DELRIN/ACETAL		10
Χ	1	1		-19		BOLT			11
1				-21		THREADED ROD	B7	M14 X 2mm (MCMASTER-CARR #93325A340) MODIFIED	12
				-23	1	THIMBLE	6061		13
				-25	1	PLACARD	PLASTIC		14
			B/O	-27	1	воттом гоам	ETHAFOAM 220, BLACK	3.95 X 9.08 X 11.98 (CASE SOLUTIONS)	15
			B/O	-29	1	TOP FOAM	ETHAFOAM 220, BLACK	1.20 X 9.08 X 11.98 (CASE SOLUTIONS)	16
1			B/O	-31		HEX NUT	STEEL	M14 X 2mm (MCMASTER-CARR #90592A032)	11
		2	B/O	-33		SOCKET HEAD CAP SCREW	STEEL	M6 X 1mm X 40mm (MCMASTER-CARR #90128A268)	2
		2	B/O	-35		FLAT HEAD PHILLIPS MACHINE SCREW	STEEL	M3 X 0.5mm X 10mm (MCMASTER-CARR #91420A120)	2
	4		B/O	-37		SOCKET HEAD CAP SCREW	STEEL	M6 X 1mm X 25mm (MCMASTER-CARR #90128A265)	6
			B/O	-39	1	CASE	PLASTIC	PELICAN #APP-1400-E	N/S
			B/O		1	PLACARD	ALUMINUM	RB41011	N/S
ASSY -19	ASSY -9	ASSY -1							

NOTE: REF. AIRBUS T/N: M633V3002101.


1:4




ELASTOMERIC BEARING BOLT EXCHANGE


RBEM633V3002102 UNLESS OTHERWISE SPECIFIED
DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ± .5°
.X ± .1 SURFACES = 125/
1. BREAK ALL SHARP EDGES
.015 x 45° OR .015R
2. DIMENSIONAL LIMITS APPLY
AFTER PLATING
3. INTERPRET DIM AND TOL PER
ASME Y14.5M-2009 MAT'L DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON
QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT H175 DATE 4/6/2016 SCALE


SHEET 1 OF 16






REVISIONS DESCRIPTION INITIAL APPROVED REV ECR DATE







SPEC

ELASTOMERIC BEARING BOLT EXCHANGE

RBEM633V3002102-5 MAT'L WHITE DELRIN/ACETAL

UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES

.XXX ± .005 FRACTIONS ± 1/8

.XX + .01 ANGLES ± .5°


.X ± .1 SURFACES = 125/


1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON


QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE

4/6/2016 SHEET 4 OF 16 1:1

	REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED	







-7

LATERAL CLAMP PLATE



ELASTOMERIC BEARING BOLT EXCHANGE

DWG NO.	RBEM633V	/3002102-7	2	
MAT'L 6061 HEAT TREAT		UNLESS OTHERWISE SPECIF DIMENSIONS ARE IN INCHE .XXX ± .005 FRACTIONS ± 1/8		
FINISH CLEAR ANODIZE SPEC MIL-A-8625F, TYPE II, CLASS I		.XX ± .01 ANGLES ±.5° .X ± .1 SURFACES = 1	25/	
		1. BREAK ALL SHARP EDGES		
DRAWN BY:	DUERFELDT	.015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY		
CHECKED:	CLOUGH	AFTER PLATING		
OPPS APPR:	ANDERSON	3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009		

4/6/2016

USED ON MODEL

H175

SHEET 5 OF 16

QA APPR:


SCALE


APPROVED:

LINDSAY

GILBERT

REVISIONS REVISIONS					
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED





NOTE:

USE APPROPRIATE ADHESIVE TO ATTACH
-17 LONGITUDINAL PAD TO -13 LONGITUDINAL
BASE PLATE.




ELASTOMERIC BEARING BOLT EXCHANGE


DWG NO. RBEM633V3002102-9 UNLESS OTHERWISE SPECIFIED DIMENSIONS ARE IN INCHES
.XXX ± .005 FRACTIONS ± 1/8
.XX ± .01 ANGLES ±.5° .XX ± .01 .X ± .1 SURFACES = 125/ SPEC 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE 4/6/2016 SHEET 6 OF 16 1:4




LONGITUDINAL ELASTOMERIC BEARING BOLT EXCHANGE



	revisions						
REV	ECR	DESCRIPTION	DATE	INITIAL	APPROVED		
2	16-0180	-13 CH'D MAT'L WAS 1018/1020 CR IS A36/1018/1020 HR.	10/20/2016	DPD	JAG		





DART


ELASTOMERIC BEARING BOLT EXCHANGE


DWG NO. RBEA	M633V3002102-13	REV 2
MAT'L A36/1018/1020 HR		
HEAT	DIMENSIONS ARE IN INC	

ACTIONS ± 1/8
ANGLES ± .5°
SURFACES = 125 TREAT
FINISH ZINC PLATE .XX ± .01 .X ± .1 SPEC ASTM B633 TYPE I SC 2 A 1.1 1. BREAK ALL SHARP EDGES .015 x 45° OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR: LINDSAY USED ON MODEL APPROVED: GILBERT H175 SCALE 1:1 4/6/2016 SHEET 8 OF 16

-13

LONGITUDINAL BASE PLATE





REVISIONS This drawing, specifications, and concepts contained here in are the sole property of Dart Aerospace, and may not be reproduced or used in any fashion without the prior written permission of Dart Aerospace Eugene, OR. DESCRIPTION INITIAL APPROVED REV ECR DATE 7.10 -ENGRAVE P/N



ELASTOMERIC BEARING BOLT EXCHANGE

RBEM633V3002102-19

MAT'L UNLESS OTHERWISE SPECIFIED TREAT
FINISH ZINC PLATE SURFACES = 125 SPEC ASTM B633 TYPE I SC 2 1. BREAK ALL SHARP EDGES .015 x 45 'OR .015R 2. DIMENSIONAL LIMITS APPLY AFTER PLATING 3. INTERPRET DIM AND TOL PER ASME Y14.5M-2009 DRAWN BY: DUERFELDT CHECKED: CLOUGH OPPS APPR: ANDERSON QA APPR: USED ON MODEL LINDSAY APPROVED: GILBERT H175 SCALE 1:1 4/6/2016 **SHEET 11 OF 16**



BOLT

